

Supybook

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME
0.0.3	2009-05-31		HH

Contents

1	Getting started	1
1.1	Initial configuration	1
1.2	Identifying to the bot	1
1.3	Accessing the online help	1
2	Understanding supybot's peculiarities	2
2.1	Nested commands	2
2.2	Plugins	2
2.3	Configuration	3
2.4	Capabilities	4
3	Administrative tasks	5
3.1	Networks	5
3.1.1	Adding a network	5
3.1.2	Reconnecting	5
3.1.3	Disconnecting	5
3.1.4	Listing networks	5
3.1.5	Adding more servers	6
3.1.6	Listing network servers	6
3.1.7	Services: NickServ	6
3.1.8	Services: ChanServ	6
3.2	Channels	7
3.2.1	Adding a new channel	7
3.2.2	Listing channels	7
3.2.3	Removing a channel	7
3.2.4	Modifying channel config	8
3.2.5	Setting the key	8
3.2.6	Setting the limit	8
3.2.7	Channel commands	8
3.2.8	Maintaining the ban list	9
3.2.9	Maintaining the ignore list	9

3.2.10	Listing channel nicks	9
3.2.11	Topic operations	9
3.2.12	Logging	10
3.2.13	Auto-ops and voices	10
3.2.14	Manipulating channel capabilities	10
3.3	Users	11
3.3.1	Adding a new user	11
3.3.2	Manipulating hostmasks	11
3.3.3	Listing users	11
3.3.4	Deleting users	11
3.3.5	Changing password	11
3.3.6	Renaming a user	11
3.3.7	Manipulating user capabilities	12
3.4	General bot maintenance	12
3.4.1	Setting nickname & alternative nick	12
3.4.2	Setting ident	12
3.4.3	Setting ircname	13
3.4.4	Setting command prefix / controlling when the bot replies	13
3.4.5	Keeping the primary nick	13
3.5	Owner commands	13
4	User commands	14
4.1	Searching the history	14
4.2	Useful plugins	14
4.2.1	Anonymous	14
4.2.2	Dict	15
4.2.3	Later	15
4.2.4	Seen	15
4.2.5	Web	16
4.3	Entertainment	16
4.3.1	ChannelStats	16
4.3.2	Games	17
4.3.3	Nickometer	17
4.3.4	Quote	17
4.3.5	QuoteGrabs	18
5	Caveats	19

6	Tips	20
6.1	How to emulate blootbot CMDs using MoobotFactoids	20
6.2	Tidier bot replies	20
6.3	More on nested commands	21
7	Reference	22
7.1	Configuration	22
7.1.1	reply	22
7.2	Directory tree	23

Preface

0.0.3

Preface

Note

At the time of this writing, Supybot version is 0.83.3. If you are using a newer (or even older) version, keep that in mind.

Note

This document is very much a work in process. It covers nowhere near everything there is to Supybot. However, it hopefully allows a good start into learning Supybot.

What is this document?

This document is a handbook for [Supybot](#), the IRC ([Internet Relay Chat](#)) bot written in Python.

Motivation behind this document

Some time ago I started needing an IRC bot for various purposes. The bot would have to be able to take care of auto-opping and similar "traditional" channel duties. This made me think of [Oer](#), an old but very nice bot. However, I also wanted to have factoid functionality similar to [bloodbot/infobot](#), without having to run multiple bots. That was when I arrived at Supybot once again. This time I decided to give it a closer look.

My experience of the documentation was lacking though. I longed for something similar to [Oer's User Manual](#) that provides a quick references for basic administrator tasks and so forth. Alas, I could not find such document.

I figured I could as well wrap up such a handbook while learning to use the bot myself. Hopefully someone finds reading this document as useful as writing it was.

Conventions used in this document

command <name> [**value**]

A command that takes `name` as a required parameter and `value` as an optional parameter.

command <nick...>

A command that takes one or more parameters.

command [--{foo,bar}] <value>

A command that takes two optional options as parameters, eg. `--foo value` and/or `--bar value`.

Plugin

A plugin name

This document is Free

This document is Free TM as defined by the [Free Software Foundation](#), more specifically, this document is available under the terms of [GNU General Public License version 3 \(GPLv3\)](#). The source is a text file that can be converted to various formats by [asciidoc](#).

How to give feedback

If you spot an error, have suggestions or just want to tell me how much you love/hate the document, send e-mail to hoxu@users.sf.net. Prefix the Subject with [supybook].

Chapter 1

Getting started

1.1 Initial configuration

Create a new directory (eg. `mkdir ~/supybot`) and run `supybot-wizard` in it. Follow the directions to get the bot initially configured.

Once you are ready with the wizard, I suggest you start the bot inside screen:

```
$ screen
$ supybot configFile
```

This way you can attach to the screen later to see the messages it writes to stdout, while still running the bot in the background. Alternative is to run it in the daemon mode, `supybot --daemon configFile`.

You can set up a crontab to start the bot automatically, for example:

```
$ crontab -e
> @reboot screen -d -m supybot /path/to/configFile
```

1.2 Identifying to the bot

After running `supybot-wizard` and starting the bot, connect to the same IRC network it is on, and `/query` it. You can identify with the `identify <name> <password>` command. You can check the bot's idea of who you are with the `whoami` command.

Note

All commands that contain a `password` must be sent to the bot in private.

1.3 Accessing the online help

Most commands on the bot have a short online help available. You can use `list` to list loaded plugins, and `list <plugin>` to list commands in those plugins. `help [plugin] <command>` can be used to access the command help. Use `more` to read long messages from the bot.

Help for configuration items can be accessed with the `config help <key>` command.

Chapter 2

Understanding supybot's peculiarities

Supybot has a couple of features that sets it apart from more traditional bots. More specifically, nested commands, plugin framework (even the basic functionality is implemented using plugins), and capabilities. This section covers some basic information about Supybot. Feel free to skip it, but come back later if you run into something you don't understand.

2.1 Nested commands

Supybot allows nested commands, in other words, you can pass the result of a command to another command as a parameter. What does this allow then, though, apart from the obvious bragging rights? For example, if you want to restore a configuration entry to the default value, you can type:

```
config reply.withNickPrefix [config default reply.withNickPrefix]
```

Obviously, that wasn't very neat. They could've included a `config reset <key>` command instead, for example. But I'm sure you can figure out **something** more useful to do with this, as a homework ;-)

2.2 Plugins

Pretty much everything in Supybot is a plugin. Most commands you use belong to a plugin. If two plugins provide the same command, then you need to prefix the command with the plugin name. For example, the `ignore list` command yields the following output:

Example 2.1 output

```
Error: The command "ignore list" is available in the Admin and Channel plugins.  
Please specify the plugin whose command you wish to call by using its name as a command ↵  
before "ignore list".
```

Thus, you need to either use `admin ignore list` or `channel ignore list` command. That is, unless you define which plugin is the default one using the `defaultplugin [--remove] <command> [plugin] command` provided in the Owner plugin.

The `list` command (Plugin) can be used to list loaded plugins. You can prevent some plugins from showing in the list with the command:

```
config plugins.<plugin>.public False
```

**Warning**

This does not really make the plugins private. They can still be listed by unregistered users (unless they have anticapability for `list`). This is a bug in my opinion.

list

List currently loaded plugins, excluding the ones set non-public.

list --private

List loaded plugins that are set to non-public.

list <plugin>

List commands provided by the given plugin.

load [--deprecated] <plugin>

Load a plugin. Supybot looks for plugins in directories listed in `config conf.supybot.directories.plugins`.

unload <plugin>

Unloads a plugin. The Owner plugin cannot be unloaded.

Note

Plugins can store information in a database. By default, the database is channel-specific. This can be changed by modifying `config databases.plugins.channelSpecific` to be global. The config item can also be set on per-channel basis.

2.3 Configuration

Most of Supybot configuration is done online using the Config plugin. This excludes things such as granting the owner capability (must be done by modifying the files).

There are two types of configuration items: global and channel-specific. The latter are actually no different from the global ones, except that they can be set for channels as well. This means you can have a global default which is overridden for specific channels.

Configuration items are hierarchical. The "root" item is `supybot`, which can be omitted. Configs for plugins live under their own key, `supybot.plugins`, or shortly, `plugins`.

config <name> [value]

Get the current value of `name`, or set it to `value` if provided.

config channel [channel] <name> [value]

Ditto, but for channel configs.

config default <name>

Get the default value of `name`. This does not change the value. No, there is no command to reset an item to default value. You need to use `config <name> [config default <name>]` for that.

config export <filename>

Export non-confidential parts of configuration to a file for debugging purposes.

config help <name>

Show help for a configuration item.

config list <group>

List configuration items in `group`. Subgroups are prefixed with `@`, channel-specific items with `#`.

config reload

Reloads configuration. Mostly useful if you've had to modify the files by hand.

config search <word>

Show configuration items matching word.

owner flush

Save configuration changes to disk. This should be done automatically as well, if the `flush` configuration item is `True` (the default).

Note

Some of the sections in this document have a list of related configuration items. They are listed similarly to the table below. In this example the config value could be modified with the `config plugin.example.foo <True|False>` command. If the key is prefixed with `#`, the config value can be set both globally and on channel-specific basis.

Table 2.1: plugin.example

Key	Default	Description
foo	True	Example key.
#bar	False	Example key that can be set on channels as well.

2.4 Capabilities

Many traditional IRC bots manage permissions of users using flags. Some network services in fact, do, too. Each user can have various flags on each channel. The flags can mean auto-op, op, use of `!ban` command and so forth. On side of those, there are often global user flags that entitle the user to full access, global auto-op, etc. Some bots also support channel flags that determine what bot functionality is available on the channel.

Supybot does not have any flags. Instead, the permissions are managed using *capabilities*. There are two kinds of capabilities: `user capabilities` and `channel capabilities`.

User capabilities are checked first when a user tries to run a command. If the user has an *anticapability* for the command (eg. `-command`, `-Plugin.command`) or the `Plugin` (`-Plugin`), it won't be run.

Next, if the command was run on the channel, the *channel capabilities* are checked. The logic is same as above, but the checked capabilities are prefixed with `#channel,`, for example `#channel,-Plugin.command`.

There are some special capabilities recognized by Supybot:

owner

For bot owners: the people who have "physical" access to the bot and its files. This cannot be granted online; the `conf/users.conf` file must be edited by hand followed by `reload`. Owners are exempt from `#channel,op` capability checks and channel anticapabilities.

admin

For bot administrators. Users with this capability can manage global bot properties, make the bot join new channels and so forth. However, they can't do channel administration which is reserved for ops.

#channel,op

Channel ops can execute channel-related commands.

trusted

Allow user to run commands that can potentially crash the bot, or cause denial of service on the system it's running on.

Commands used to manipulate capabilities are covered in the [Manipulating channel capabilities](#) and [Manipulating user capabilities](#) sections.

Chapter 3

Administrative tasks

3.1 Networks

Related plugins: Network, Services.

3.1.1 Adding a network

network connect [--ssl] <network> [<host[:port]>] [password]
Connect to *network*. *host* must be provided if the network is new or has no servers defined.

3.1.2 Reconnecting

reconnect [network] [message]
Disconnects and connects *network*, or current if not specified. *message*, if given, is shown as the quit message, otherwise `config plugins.Owner.quitMsg` is used, or your nickname.

3.1.3 Disconnecting

network disconnect [network] [message]
Disconnect *network*, or current if not specified. *message* as above.

3.1.4 Listing networks

networks
List of networks & servers currently connected to.

Example 3.1 output

```
freenode: wolfe.freenode.net and ircnet: irc.elisa.fi
```

config list networks
List all networks.

3.1.5 Adding more servers

Once you've added a network with the initial server, you can add more servers:

```
config networks.<network>.servers [config networks.<network>.servers] server:6667
```

3.1.6 Listing network servers

```
config networks.<network>.servers
```

Example 3.2 output

```
chat.freenode.net:6667
```

3.1.7 Services: NickServ



Warning

My practical experience with Services plugin on Freenode is... not-so-good. It definitely does not work all the time as expected.

You can make Supybot identify itself to the network NickServ after it has connected.

config plugins.Services.noJoinsUntilIdentified True

Settings this is useful on Freenode and other networks who change the user mask after identifying to NickServ. In my experience this seems to be a tad buggy, so I don't recommend enabling it unless really needed.

config plugins.Services.NickServ NickServ

Tell the bot what name NickServ can be found under.

services password <nick> [password]

Can be used to set or remove NickServ password.

NOTE: Password removal did not work for me on Supybot 0.83.3

services identify

Identifies the bot to NickServ with the current nick. You don't need to give this command after the bot has been set up; it will identify when connecting to the network automatically.

3.1.8 Services: ChanServ

You can make Supybot request op after joining a channel on a network with ChanServ.

config plugins.Services.ChanServ ChanServ

Tell the bot what name ChanServ can be found under.

config plugins.Services.ChanServ.op <on|off>

Set the default for all channels. This will be used unless a channel-specific config overrides it.

config channel [channel] plugins.services.ChanServ.op <on|off>

Set to request op on the given channel.

Voice and half-op (on networks supporting it) can be used similarly.

3.2 Channels

Related plugins: Channel.

Note

Commands in this section (such as adding/removing channels) work in the current network, eg. the one you are messaging the bot in. The commands also accept a `[channel]` parameter which is needed only when the command is written in private.

Note

If you want to `/msg` the bot in one network, while having the command apply in another network, you can use the `network` command `<network> <command> [params] command`. The reply comes in the other network if you are there as well.



Warning

The `network` command does not seem to check if the user having your nick in the other network is recognized (eg. identified or recognized by hostmasks), so the reply may end up to someone else.

3.2.1 Adding a new channel

join `<channel> [key]`

Joins the `channel` using `key` if provided. Channels are automatically remembered and joined when the bot connects to the network next time.

Note

`config plugins.Channel.alwaysRejoin` determines whether the bot will (attempt to) rejoin the channel when kicked out (the default).

3.2.2 Listing channels

`channels`

Note

This only works in private, to prevent knowledge of top secret channels from falling into wrong hands.

You can list channels in another network with `config networks.<network>.channels`. Or with `network` command `<network> channels`.

3.2.3 Removing a channel

part `[channel] [reason]`

Makes the bot leave `channel`, showing `reason` as part message if given. Note that all channel data is retained, but the bot does not join the channel anymore the next time it connects to the network.

3.2.4 Modifying channel config

config channel [channel] <name> <value>

Sets config item `name` on `channel` to `value`, overriding the global value.

3.2.5 Setting the key

channel key [channel] [key]

Sets key on `channel` to `key`, or removes it if `key` is not given.

3.2.6 Setting the limit

channel limit [channel] [limit]

Sets limit on `channel` to `limit`, or removes it if `limit` is not given (or is zero).

3.2.7 Channel commands

Channel ops can use the following commands to control the channel via the bot, assuming it is opped.

op [channel] [nick...]

Ops the given nicks (or you if none) on the channel.

deop [channel] [nick...]

Ditto, but deops.

voice [channel] [nick...]

Voices the given nicks (or you if none) on the channel.

devoice [channel] [nick...]

Ditto, but devoices.

kban [channel] [--{exact,nick,user,host}] <nick> [seconds] [reason]

Bans and kicks the given nick from the channel. If `seconds` is specified and is not 0, the ban will expire after that time.

mode [channel] <mode> [params]

Set channel mode. This can be used to change any channel modes, making the commands below redundant aliases.

moderate [channel]

Set +m. This is not enforced by the bot, so any channel op can remove it.

unmoderate [channel]

Set -m.

topic lock [channel]

Set +t. Not enforced, so any channel op can remove it.

topic unlock [channel]

Set -t.

alert [channel] <text>

Sends `text` to all users on the channel with op capability.

cycle [channel]

Make the bot part and join the channel. Mostly useful to test whether auto-ops from other bots/users work for the bot.

3.2.8 Maintaining the ban list

ban add [channel] <nick|hostmask> [expires]

Add ban for given nick or hostmask on the channel. If nick is given, the full hostmask is banned. `expires` when gives, expires the ban after so many seconds.

ban list [channel]

List bans with their expire times.

ban remove [channel] <hostmask>

Removes the ban on given hostmask.

config plugins.Channel.banmask <string>

Hostmask style for `ban add`: `exact`, `nick`, `user`, `host`. This means which parts of the nick's current hostmask are used (rest are wildcarded). Default is `host user` (eg. `*!user@host`).

Note

Users matching the ban list are not automatically kicked off the channel. See the `kban` command in the previous section to kick and ban a user.

3.2.9 Maintaining the ignore list

channel ignore add [channel] <nick|hostmask> [expires]

Ignores hostmask (or the full hostmask nick currently has) on channel. If `expires` is given, the ignore expires after that many seconds.

channel ignore list [channel]

Show ignored hostmasks on channel. This does not show the expire times, though (argh!).

channel ignore remove [channel] <hostmask>

Remove hostmask from list of ignored hostmasks on channel.

Note

There is also a global ignore list, available for admins.

3.2.10 Listing channel nicks

`channel nicks` [channel]

3.2.11 Topic operations

Related plugins: `Topic`.

Supybot allows elaborate manipulation of the channel topic.

<http://supybot.com/documentation/plugins/topic>

3.2.12 Logging

Logging of channels is provided by the ChannelLogger plugin. Various channel-specific configuration items are provided, see `config list plugins.ChannelLogger`.

By default logs will go into `logs/ChannelLogger/<network>/<channel>/<channel>.log` and will be rotated when the default `"%d-%a-%Y"` (eg. 06-Sat-2008) timestamp rotates. See [the python documentation for strftime](#) for the formatting characters.

Note

The logs of ChannelLogger cannot be searched online. However, other plugins provide some searching functionality. See [Searching the history](#).

3.2.13 Auto-ops and voices

Auto-opping is provided by the AutoMode plugin.

load AutoMode

Loads the AutoMode plugin, which works out-of-box. By default it's enabled on all channels and voices/halfops/ops users with respective capabilities. You can enable auto-opping only on some channels by tweaking the config keys below.

Table 3.1: `plugins.AutoMode`

Key	Default	Description
<code>#enable</code>	True	Whether the plugin is enabled.
<code>#fallthrough</code>	False	If enabled and <code>op</code> is False, halfops/voices instead if they are True.
<code>#halfop</code>	True	Halfop users with the <code>halfop</code> capability.
<code>#op</code>	True	Ditto, but <code>op</code> .
<code>#voice</code>	True	Ditto, but <code>voice</code> .
<code>#ban</code>	True	Whether to ban people who join the channel and are on the banlist.
<code>#ban.period</code>	86400	How many seconds bans will last.

3.2.14 Manipulating channel capabilities

`capability list [channel]`

List capabilities on channel.

`capability set [channel] <capability..>`

Adds the given `capability` to channel.

`capability unset [channel] <capability..>`

Removes the given `capability` from channel.

`capability setdefault [channel] <True|False>`

Whether to allow users on `channel` by default to access non-maintenance related commands. Default is True. Note that this concerns unregistered users as well. So if you want to disallow use of commands by unregistered users, set default user capabilities to allow them, and set this to False.

See also [Capabilities](#).

3.3 Users

Related plugins: Users.

Supybot users are global: they are visible across networks. This means the same username/password and hostmasks will work in all networks the bot is on.

Users are recognized either by matching hostmasks, or after manually identifying to the bot. In secure mode, the user must both match a hostmask and identify to the bot (`uset set secure [password] <True|False>`).

Note

If users knowing each others' nicks is an issue, they could come up with different aliases when registering to the bot. The bot username does not have to match the nick of the user.

3.3.1 Adding a new user

```
user register <name> <password>
```

3.3.2 Manipulating hostmasks

`user hostmask add` - add your current hostmask. Obviously this makes only sense after identify.

`user hostmask add [name] [hostmask] [password]` - add hostmask for another user. If not owner, password must be given.

```
user hostmask remove <name> <hostmask> [password]
```

Note

There is no way to add network-specific hostmasks.

3.3.3 Listing users

`user list [glob]` - list registered users. Note that the list of users is global across networks.

3.3.4 Deleting users

```
user unregister <name> [password]
```

3.3.5 Changing password

```
user set password <user> <old password> <new password>.
```

3.3.6 Renaming a user

```
user changename <name> <new name> [password]
```

Users can change their name themselves.

3.3.7 Manipulating user capabilities

capabilities [user]

List capabilities of the user, or the calling user.

admin capability add <user|hostmask> <capability>

Add capability to user or a user that matches the hostmask.

admin capability remove <user|hostmask> <capability>

Ditto, but remove the capability.

channel capability add [channel] <nick|user> <capability..>

Add capability capability on channel to nick/user.

channel capability remove [channel] <nick|user> <capability..>

Remove capability capability on channel from nick/user.

defaultcapability <add|remove> <capability>

Add or remove capability from list of capabilities given to new users.

config capabilities

List default capabilities given to new users.

Example 3.3 output

```
-owner -admin -trusted
```

See also [Capabilities](#).

3.4 General bot maintenance

Related plugins: Admin, Config.

3.4.1 Setting nickname & alternative nick

admin nick <newnick>

Change nick to newnick.

config nick

Default nick.

config nick.alternates

Space-separated list of alternate nicks, %s refers to nick.

Note

It is not possible to have a different nick in different networks.

3.4.2 Setting ident

config ident <newident>

Sets the bot's ident (nick!ident@host).

3.4.3 Setting ircname

config user [ircname]

Sets the bot's ircname/realname to `ircname`. If left empty, defaults to *Supybot 0.83.3* for example.

3.4.4 Setting command prefix / controlling when the bot replies

Like most other bots, the bot can be addressed by its nickname, or a command prefix character (any or many of `~!@#$%^&*()_-=[]{}`). For special (braindead?) purposes the bot can also be made assume that all lines are addressed to it.

config reply.whenAddressedBy.chars

List of characters the bot will recognize as addressing, besides the nick of the bot.

config channel [channel] reply.whenAddressedBy.chars

Ditto, but for a specific channel.

config reply.whenNotAddressed

Assume everyone wants to talk to the bot, eg. treat all messages as if addressed to the bot. This does not imply `reply.WhenNotCommand False` which you should set as well.

config reply.whenNotCommand

Whether to reply when addressed with an invalid command.

See also: [Configuration: reply](#).

3.4.5 Keeping the primary nick

Like other bots, Supybot can be configured to try and keep the primary nick using the NickCapture plugin. This is primarily useful in networks with no NickServ support.

load NickCapture

Loads the plugin which works without further configuration.

config plugins.NickCapture.ison

Whether the plugin is actively checking for the primary nick. This setting makes no sense, as you might as well unload NickCapture if you think about setting this to false.

config plugins.NickCapture.ison.period

How many seconds to wait between nick availability polls. The default is 600 (10 min). The smaller you set this, the higher the chance of the bot recovering the nick when it becomes available. On the other hand, you will also generate more traffic so you might want to avoid that.

3.5 Owner commands

`owner announce <text>` - send text to all channels the bot is on.

`owner ircquote <raw>` - send raw as-is to the server. You need to know your way around [RFC1459](#) pretty well to use this.

Chapter 4

User commands

4.1 Searching the history

url last [**channel**] [--{**from,with,without,near,proto**} **value**] [--**nolimit**]

Find last URL (or all with `--nolimit`) matching given criteria. From matches nick, with(out) part of the URL, near rest of the line where the URL was, and proto matches the protocol (https, ftp, etc). In case of multiple URLs, the newest is listed first. Multiple criterias can be given.

NOTE: This command lists only the URLs, not nick or what message the URLs were part of

last [--**from,in,on,with,without,regexp**] **value**] [--**nolimit**]

Find messages matching given criteria. From matches nick, in matches channel, on matches network, with(out) matches part of the message, regexp matches messages that are included by the regular expression. Also see `config protocols.irc.`

4.2 Useful plugins

4.2.1 Anonymous

Allows you to provide users a way to chat on a channel anonymously (eg. only the bot owner(s) know via logs who are talking).

do <channel> <action>

Sends `action` to `channel`. This is the same as a normal IRC client `/me does something command`.

say <channel> <text>

Say `text` on `channel`.

Table 4.1: plugins.Anonymous

Key	Default	Description
<code>#requirePresenceInChannel</code>	<code>True</code>	Whether the user must be in the channel the message is targeted to.
<code>allowPrivateTarget</code>	<code>False</code>	Whether to allow a nick as a target for say. NOTE: This has not been implemented in 0.83.3 although it exists!
<code>requireCapability</code>		If set, capability to check for.
<code>requireRegistration</code>	<code>True</code>	Whether registration is required to use this plugin.

4.2.2 Dict

Dict provides dictionary functionality using dict.org. You can also use a local dictd server.

dict [dictionary] <word>

Show dictionary entry for `word`, from `dictionary` if provided. If `plugins.Dict.default` is set, use the specified dictionary instead of all.

dictionaries

List dictionaries available on the used server.

dict random

Show a random dictionary from available dictionaries.

config plugins.Dict.server [server]

The dictd server to be used, default is dict.org.

config plugins.Dict.default [dictionary]

Channel-specific default dictionary for `dict` command. `*` means to use all dictionaries. `wn` is a good default if english words are mostly looked up.

4.2.3 Later

This is a nick-based replacement for NoteServ and the likes. Simply put, you give the bot a note to deliver to a nick (or wildcard) the next time it sees a matching nick. In other words, this can be used to deliver messages to people who are not registered to the bot. Naturally that is not a very safe method of communicating.

notes [nick]

List nicks that have notes queued, or the notes queued for `nick` if given.

later tell <nick> <text>

Queues `text` to be sent to first matching `nick` when seen. Nick can contain wildcards, eg. `foo*`.

config plugins.Later.maximum

How many messages can be queued per nick at maximum, default is 0 = no limit.

config plugins.Later.private

Whether to send notes in private or on the channel where the recipient is seen.

4.2.4 Seen

The Seen plugin keeps track of last channel/nick/user activity. Most typical use is asking the bot when a given user was last seen chatting on a channel.

seen any [channel] [--user <user>] [nick]

Lists any activity given `nick` or `user` was doing on the channel. If no `nick` or `user` is given, returns the last activity on the channel, regardless of who it was from.

seen last [channel]

Last line said on the channel.

seen [channel] <nick>

Last time a `nick` was seen on a channel and what it said.

`seen user [channel] <user>`: Ditto, except use a user name, disregarding what nick the said user had.

4.2.5 Web

The Web plugin contains some useful WWW-related functionality, such as fetching titles for URLs users paste on the channel.

doctype <url>

Show the doctype line of url, if any.

fetch <url>

Show the contents of url. Amount of data shown is determined by the configuration variable `plugins.Web.fetch.maximum`.

headers <url>

Show web server headers for the url.

netcraft <hostname|ip>

Ask netcraft what OS and web server it thinks the server is running.

size <url>

Show size of url, based on the Content-Length header sent by the web server.

title <url>

Show title for url. This can be done automatically for all URLs pasted on a channel; see the configuration variable `plugins.Web.titleSnarfer`.

urlquote <text>

Return text quoted into a URL. Eg. `urlquote foo bar` → `foo%20bar`.

urlunquote <text>

Likewise, but reverse.

Table 4.2: `plugins.Web`

Key	Default	Description
<code>#nonSnarfingRegex</code>		if set, URLs matching the pattern are not snarfed.
<code>#titleSnarfer</code>	<code>false</code>	Whether to fetch and show the title for pasted URLs.
<code>fetch.maximum</code>	<code>0</code>	Maximum bytes to fetch with the <code>fetch</code> command. If zero, <code>fetch</code> is disabled.

4.3 Entertainment

4.3.1 ChannelStats

ChannelStats provides channel/registered user statistics (statistics as in *large numbers*).

`channelstats` [channel]: Show statistics for channel: messages, characters, words, smileys, frowns, actions, joins, parts, quits, kicks, mode changes, and topic changes.

`stats` [channel] [user]: Show statistics for user on channel: messages, characters, words, smileys, frowns, actions, joins, parts, quits, kicks given/received, topic changes, and mode changes.



Warning

This plugin may turn otherwise normal users into spammers. But it can also provide an incentive to register on the bot. :-)

Table 4.3: plugins.ChannelStats

Key	Default	Description
#frowns	: :-/ :-\ :\ :/ :(:-(:' (Space-separated list of frowns.
#selfStats	True	Whether to include the bot in the statistics.
#smileys	:) ;) ;] :-) :-D :D :P :p (= =)	Space-separated list of smileys.

4.3.2 Games

coin

Heads or tails?

dice <dices>d<sides>

Roll `dices` dices, each having `sides` sides. Lists result for each dice separately. The sum will be between `dices` and `dices x sides`.

eightball [question]

Answers a question. But don't expect the bot to pass

monologue [channel]

Check how long your monologue on the `channel` is, in case you are lose count. This is probably my favourite useless command.

roulette ["spin"]

Russian roulette. If `spin` is given, spins the chambers. This isn't really necessary since it will be done automatically at the end of the round. Provides a different experience if the bot is opped.

4.3.3 Nickometer

`nickometer [nick]`: Give an objective evaluation on the lameness of `nick`, or your nick if not provided. This is similar to the same command in `blootbot`.

Example 4.1 output

```
The "lame nick-o-meter" reading for "1eEteStWaReZL0rD[69X~" is 99.98%.
```

4.3.4 Quote

quote add [channel] <text>

Add `text` as a quote for `channel`.

quote change [channel] <id> <regexp>

Change quote `id` on `channel` using `regexp`. For example, `s/foo/bar/g` changes all instances of `foo` to `bar`.

quote get [channel] <id>

Show quote # `id` for `channel`.

quote random [channel]

Show random quote from `channel`.

quote remove [channel] <id>

Remove quote # `id` from `channel`.

quote search [channel] [--{regex,by} value] [glob]

Find quotes from `channel` matching `regex` if provided, added by `nick` if provided, and matching `glob` if provided. `glob` may contain wildcards (eg. `foo*bar`), while `regex` is a regular expression (eg. `/la.*laa/`). Note that you can really provide both `regex` and the `glob` - both must match in that case.

quote stats [channel]

Show how many quotes there are.

4.3.5 QuoteGrabs

This plugin allows users to *grab* the most recent line of another nick as a quote.

quotegrabs get [channel] <id>

Show quote # `id`.

quotegrabs grab [channel] <nick>

Save last line from `nick` as a quote.

quotegrabs list [channel] <nick>

List quotes for `nick`, newest first. This does not display full quotes, but part of each, along with the `id`.

quotegrabs quote [channel] <nick>

Show last quote of `nick`.

quotegrabs random [channel] [nick]

Random quote from any nick, or `nick` if provided.

quotegrabs search [channel] <text>

Show quotes containing `text`. Unfortunately, this does not list the nick or allow searching only given nick's quotes. `id` and quote content will be shown.

Table 4.4: plugins.QuoteGrabs

Key	Default	Description
<code>#randomGrabber</code>	<code>False</code>	Whether to grab random lines as quotes.
<code>#randomGrabber.averageTimeBetweenGrabs</code>	<code>86400</code>	Average number of seconds to wait between random grabs. When half of this has passed a random grab may occur.
<code>randomGrabber.minimumCharacters</code>	<code>8</code>	Minimum characters needed to consider a line eligible for random grab.
<code>randomGrabber.minimumWords</code>	<code>3</code>	Ditto, but for words.

Chapter 5

Caveats

This is a list of issues I have not yet figured out how to do, or there simply isn't a way.

- How to enforce channel modes (eg. force +ns-t for example)
 - How to delete config items
 - How to delete channels / networks
 - Ban add does not seem to work on Freenode
 - No global ban list
 - No way to delete a network
 - Incomplete multi-network support
 - Capabilities are not network/channel -specific, but channel-specific. If channel by same name exists in two networks, the users have same capabilities on both
 - No way to add network-specific hostmasks
 - Not possible for the bot to have different nick in different networks
 - There is no command to reboot the bot; it must be done from the shell
 - Capabilities/anticapabilities for commands with spaces in them are not supported
-

Chapter 6

Tips

6.1 How to emulate blootbot CMDs using MoobotFactoids

Thanks to Tobias "beardy" Rosenqvist for the tip!

We try to make a command factoid, like we are used to with blootbot:

```
<user> cmdtest is <action> gives $1 "(an apple|a pear)"
<bot> Ok.
```

Then we test it:

```
<user> cmdtest someone
```

But it doesn't work. However, the factoid works:

```
<user> cmdtest
* bot gives $1 an apple
```

The Moobotfactoids plugin in supybot doesn't handle arguments, (yet) unfortunately, so you need to do it another way. Use the Moobotfactoids to do the random part(s):

```
<user> fruits is <reply> "(an apple|an orange|a banana|a pear)"
<bot> Ok.
```

Then use an alias to do the command, with arguments (the "action" command is found in the Reply plugin), here you also see a use of a nested command:

```
<user> alias add givefruit action gives "[fruits]" to $1
<bot> Ok.
<user> givefruit someone
* bot gives a pear to someone
```

6.2 Tidier bot replies

I don't personally like the default Supybot replies: I hate the nick prefix and the way too verbose *The operation succeeded.*

Fortunately there are plenty of settings to configure how Supybot replies. These can be listed with `config reply` and `config replies`.

The `reply` items determine how Supybot acts, and `replies` contains some messages it uses. I prefer:

```
config reply.withNickPrefix False
config replies.success OK
config reply.error.inPrivate True.
```

6.3 More on nested commands

Thanks to Tobias "beardy" Rosenqvist for the tip!

For those familiar with unix shells, (bash in particular), nested commands can be compared to doing command substitution, as in `$(command)`.

Nested commands are by default enclosed by square brackets (`[]`). The `commands.nested.brackets` configuration variable can be used to set these to `<>`, `{}`, or `()`.

```
<user> echo The title of the Supybot website is: [web title http://www.supybot.com/]
<bot> The title of the Supybot website is: Welcome to Supybot.com! Supybot Website
```

Another way nested commands can work, is like a pipe, if the configuration variable `commands.nested.pipeSyntax` is set to `True`.

Same example as above, but using the pipeSyntax:

```
<user> web title http://www.supybot.com/ | echo The title of the Supybot website is:
<bot> The title of the Supybot website is: Welcome to Supybot.com! Supybot Website
```

Chapter 7

Reference

7.1 Configuration

7.1.1 reply

#inPrivate	Whether to reply in private to commands given on channel.
#requireChannelCommandsToBeSentInChannel	
#showSimpleSyntax	Whether to be extra helpful when a user fails syntax of a command.
#whenNotAddressed	Assume everyone wants to talk to the bot, eg. treat all messages as if addressed to the bot. This does not imply <code>reply.WhenNotCommand False</code> which you should set as well.
#whenNotCommand	Whether to reply when addressed with an invalid command.
#withNickPrefix	Whether to prefix the reply with the nick of the user who gave the command.
#withNotice	Whether to use notices instead of regular messages.
#mores.instant	How many messages to send initially before prompting for <code>more</code> . Default is 1.
#mores.length	How long messages can be. Default is 0, which uses rocket science to determine the maximum number of characters that can be fit into a message without it collapsing into a black hole.
#mores.maximum	Maximum number of messages to queue, default is 50.
#error.inPrivate	Whether to send errors in private instead of replying on channel.
#error.noCapability	If True, don't tell users why they can not run a command because of missing capabilities.
#error.withNotice	Whether to send errors as notices instead of regular messages.
error.detailed	Whether to show an exception or a generic error when something breaks. Mostly useful for developers.

#format.time	Format string for timestamps (%I:%M %p, %B %d, %Y, eg. <i>08:41 PM, September 11, 2008</i>).
#whenAddressedBy.chars	List of characters the bot will recognize as addressing (when a command is prefixed with one of them), besides the nick of the bot.
#whenAddressedBy.nicks	List of extra nicks to consider as addressing the bot, despite the current nick.
#whenAddressedBy.strings	Like the chars key, except a space-separated list of strings to accept as command prefix. This allows multicharacter command prefixes.
#whenAddressedBy.nick.atEnd	Whether to consider messages that end in the bot's nick to be addressed to the bot.
maximumLength	Maximum length of a reply message from the bot. This does not mean the length of a single message (prompting for <code>more</code>), but the whole message.
oneToOne	Whether to send replies consisting of multiple messages in a single message.
withNoticeWhenPrivate	Whether to use notices instead of private messages.

7.2 Directory tree

This section contains list of the directories and files supybot uses, and what they are for.

Note

If you modify the configuration files by hand when the bot is running, you need to run `config reload`.

backup/

For backups of config files.

conf/

Configuration files: {channels,ignores,userdata,users}.conf

data/

Plugin databases.

data/#channel/

Channel-specific plugin databases.

data/tmp/

Temporary plugin data files (eg. database journals).

logs/

Logs.

logs/ChannelLogger/

ChannelLogger logs. The structure depends on the config variables.

logs/messages.log

The main logfile.

plugins/

Local plugin directory. This is by default listed in `config directories.plugins`.

<bot>.conf

The main configuration file of the bot.

tmp/

Temporary files.
